



H27i



Two strong design advantages—front-cut mowing and Kohler’s Delphi electronic fuel injection system—have been brought together in the H27i. It is ideal combination of horsepower, productivity and fuel efficiency.

- 27-HP, Electronic Fuel Injection (EFI) Kohler OHV V-Twin, air-cooled
- Remote Cummins Filtration OptiAir™ with remote Enginaire precleaner for increased engine life
- Dual, independent Hydro-Gear® ZT3400 transaxles
- Deep deck design delivers Walker’s trademark precision cut
- Tilt-up style body completely exposes drive train
- Splined PTO drive shaft with quick-disconnect coupler
- Contoured seat with armrests and full adjustable suspension
- Foot operated deck height adjustment
- Dual 4.7 gal. fuel tanks with easy-to-use fuel selector valve
- 10 mph ground speed
- Deck Sizes: Rear Discharge 52", Side Discharge or Mulching 60"
Optional decks with deck arm adapter kit: Side Discharge 48", 52", 56", 62", 74", Mulching 48", 52"



more info at
walkermowers.com

Key Engine Specifications		Popular Options	
Manufacturer/Model	Kohler Command Pro, ECH749, EFI	ROPS Kit	All-Trail Drive Tires
Displacement	747 cc (45.6 cu in)	Headlights	
Max Power	26.5 hp @ 3600 rpm	Tail Weight	
Max Torque	44.3 ft lbs		
Fuel	Gas (E10 Max)		
Fuel Capacity	9.4 gal (36 liter)		
Fuel Consumption	1.17 gal (4.43 liter)/hour		
Cooling System	Air		
Lubrication System	Full Pressure w/ Filter		
Quick Reference Dimensions		Compatible Implements/Attachments	
Tractor	753 lbs.	60" Dozer Blade	H-Series: 60" Rotary Broom
Tractor & Deck ¹¹	1,198 lbs., 46.5" H x 62" W x 107" L	H-Series: Implement Hitch	
		H-Series: 50" Two-Stage Snowblower	

¹¹Dimensions and weight shown with 60" deck with discharge shield folded